For Earth, For Life



KUBOTA F-SERIES

F-251



Guaranteed to help you master any task

If you are looking for a front mower that performs its mowing tasks as quickly as it does neatly, Kubota's F-251 is the perfect choice. This machine offers impressive area performance as well as high-quality mowing and mulching. This results in an excellent power-to-cost ratio.



Model	Engine	Power (SAE J1995) hp	Transmission	Mowerdeck	Туре	Mulching kit
F251	D1105	25	HST 4WD	RCK60 or RCK60R	Side discharge or rear discharge	Yes as option

#Features



Powerful engine

The Kubota diesel engines comply with the most recent EU Stage V emissions directive and deliver a respectable 25 hp. This makes even heavy work easy, such as mowing and collecting high and wet grass.





Reliable transmissions

The dual range HST hydrostatic transmission is very efficient and is operated with a single pedal. The four-wheel drive version of the F-251 is equipped with automatically assisted 4WD. When the conditions require it, four-wheel drive is automatically engaged. You can also select the permanent 4WD mode.



Ergonomic operator platform

The comfortable, ergonomic operator's platform literally puts everything at your fingertips, because all the controls are perfectly positioned. You can also set the adjustable steering wheel to the position that suits you best. The instrument panel is clear and easy to read.



Perfect multi-function machine

The F-251 offers a load capacity of 260 kg on the lower links. Together with a 2,545 rpm PTO, this means you can equip this machine with a mower, flail mower, sweeper and much more.



Improved mulching quality

The new mower deck features impressive increased cutting performance. The updated design creates an improved airflow, which results in better mulching quality.

#Technical data

SAE KW (PS)	F-251		
CAF IAM (DO)	D1105		
CAE LAW/DO			
57L 100 (105)	Indirect injection, vertical, water-cooled, 4 cycle diesel		
<u> </u>	3		
cm ³	· ·		
	·		
	61		
<u>'</u>	O1		
Front	24 x 12–12 (4PR) turf		
	18 x 9.5–8 (6PR) turf		
neverse riigii km/n	Power, hydrostatic		
	Main – hydrostatic transmission, high-low gear shift (2 forward/2 reverse)		
	Wet disk type		
mm	750 (inside of front tyre)		
	Bevel gear		
	Bevel gear		
neai	Dual-acting overrunning 4WD		
	Dual-acting overturning 444D		
min-1 (rpm)	2,545 (1 speed)		
min ⁻¹ (rpm)	2,545 (Shaft drive, Kubota 10 tooth involute spline)		
	Wet multi plates		
	Wet single plate		
	3 - 1		
ut mower deck mm	2,450		
ut mower deck mm	1,370		
without ROPS mm	1,350		
with ROPS mm	1,985		
mm	1,300		
ce mm	185		
Front mm	1,063		
Rear mm	1,020		
without mower deck kg	741		
18			
	RCK60-F251EU RCK60R-F251EU		
	3		
mm (inch)	1,520 (60)		
	Side discharge Rear discharge		
	25–129 (1–5)		
min (inch)	Universal joint shaft drive		
	Oniversal joint shart drive		
	2 point linkage		
	ut mower deck mm It mower deck mm Without ROPS mm Ce mm Gear mm without mower deck kg mm (inch)		

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

