

For Earth, For Life
Kubota

BV

**KUBOTA
BV PLUS SERIES**





Plus Series Variable Chamber Balers

The latest Kubota PLUS series BV balers combine profitable high output performance with market leading bale density. They benefit from a host of upgrades designed to boost output and reduce maintenance requirements, keeping operating costs to a minimum.



+ **Increased Feeding Capacity**

New roller crop press with increased lifting of the roller. Updated side support arms, new lower limit stops and fixed shafts with internal bearings providing improved protection.

+ **Enhanced Crop Flow**

New upgraded pick-up with longer pick-up tines and wider stripper plates for improved cleaning. Increased size and specification of pick-up drive chains with upgraded tensioners.

+ **Low Maintenance Driveline**

All bale chamber drives are equipped with heavy duty HBC specification chains, providing higher fatigue strength & increased wear resistance.

+ **Ultimate Reliability**

Rugged new Idler roller design with 45% increase in bearing diameter, larger internal grease capacity and improved shielding. A continuous central shaft also provides enhanced rigidity.

+ **Simplified Maintenance**

Bale chamber drive rollers with cast iron housings and centralised grease banks, ensure non-productive maintenance time is kept to a minimum.

+ **Enhanced Visibility**

New high level LED road light units mounted up out of harms way for reduced likelihood of damage from stray bales.

+ **Operator Convenience**

New improved foldable PTO stand also incorporates handy hose and cable storage. New easy access rear PTO cover for easier maintenance.

Control Terminals:



Focus 3 NON ISOBUS

Simple and easy-to-use interface.



NEW Tellus GO + ISOBUS

With a 7-inch touch screen allowing quick and easy machine set-up and control.



Tellus PRO - ISOBUS

Control the baler via the interface in the top screen.

PowerBind Net Wrap

PowerBind direct net injection for fast and highly reliable netting. Also featuring very low loading height for maximum convenience and time saving.

Intelligent Density 3D

Fully programmable bale density setting with three pre-selectable options for silage hay and straw easily set from the control box.

Wide 2.2m low profile Pick-Up & High capacity intake systems

Options of PowerFeed rotor intake or SuperCut 14 and 25 knife systems for accurate pre-chopping for optimal silage quality.

Control System

ISOBUS controls for easy and intuitive control and monitoring of main functions. All important settings are made from the comfort of the tractor cab.



Superior Bale Quality

Bale formation with five belts and three rollers provides dense, well shaped bales. Versatile multi-crop performance in silage, hay or straw.

Parallelogram DropFloor

Parallelogram drop floor system brings faster and easier clearing of blockages from the comfort of the tractor cab.

The Variable Chamber Plus Series Baler Range



RV5100 PLUS



RV5200 PLUS



RV5200 PLUS FlexiWrap

Model	BV4160 Plus	BV4180 Plus	BV5160 Plus	BV5200 Plus	BV5160 Plus FlexiWrap	BV5200 Plus FlexiWrap
Bale chamber						
Bale dimensions (m)	1.20 x 0.80-1.65	1.20 x 0.80-1.75	1.20 x 0.60-1.65	1.20 x 0.60-2.00	1.20 x 0.60-1.65	1.20 x 0.60-2.00
Specification						
Fork Feeder	●	●	-	-	-	-
DuoFeed Fork Feeder	●	●	-	-	-	-
PowerFeed Rotor	●	●	●	●	-	-
Net	●	●	●	●	●	●
Double	●	●	●	●	-	-
SuperCut 14 knives	-	-	●	●	●	●
SuperCut 25 knives	-	-	●	●	●	●

- not available ● standard

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.

® = trade mark protection in the EU.

©2020 Kverneland Group Ravenna.Srl

The Kubota logo is rendered in a teal color. It features the word "Kubota" in a stylized, rounded font. The letter 'K' is particularly large and bold, with a unique shape. The 'u' and 'o' are also stylized, with the 'o' having a small gap at the top. The 'b' is thick and solid. The 't' is simple and vertical. The 'a' is rounded and ends in a small tail. A registered trademark symbol (®) is located at the bottom right of the logo.

Visit our web site at: www.kubota.co.uk

Kubota Plus series 2020-EN. Printed 06.2020